



COUNTY OF
IMPERIAL

DEPARTMENT OF
PUBLIC WORKS

155 S. 11th Street
El Centro, CA
92243

Tel: (442) 265-1818
Fax: (442) 265-1858

Follow Us:



[www.facebook.com/
ImperialCountyDPW/](http://www.facebook.com/ImperialCountyDPW/)



[https://twitter.com/
CountyDpw/](https://twitter.com/CountyDpw/)



Public Works works for the Public

COUNTY OF IMPERIAL PUBLIC WORKS

Heber Townsite Improvements for Various Roads – Phase II County Project No. 7135CAPP

ADDENDUM NO. 2

July 30, 2025

This *ADDENDUM* is hereby made part of the Contract Documents and specifications to the same extent as if originally included therein, and shall be signed by the Bidder and included with the proposal.

1. **REPLACE the Bid Item List on Page 2 of the Notice to Bidders of the project specifications with the revised Page 2 Bid Item List attached to this Addendum.**
2. **REPLACE the Bid Item List on Page 65 of the Division XIV Bid Proposal of the project specifications with the revised Bid Item List Page 65 attached to this addendum.**

John A. Gay, P.E.
Director of Public Works

Acknowledgement of Addendum No. 2

The general contractor is responsible for advising any and all subcontractors of this change. Each bidder must acknowledge receipt of this addendum in the noted space below and where indicated on the Bidder's Proposal Section of the Special Provisions. This Addendum must be attached to the proposal.

License No: _____

Print or Type Company Name: _____

Print or Type Authorized Name: _____

Authorized Signature of Contractor: _____

Date Signed: _____

BID ITEM LIST

ITEM NO.	ITEM	UNITS OF MEASURE	ESTIMATED QUANTITY
1	Mobilization	LUMP SUM	1
2	Clearing and grubbing	LUMP SUM	1
3	Pot-hole existing utilities	LUMP SUM	1
4	Sawcut the existing A.C. pavement for the full depth.	L.F.	4,230
5	Cold plane existing A.C. pavement for a thickness of 0.20' min. Contractor to dispose of grindings.	S.F.	8,455
6	Remove and dispose of existing A.C. pavement.	C.Y.D.	625
7	Earthwork cut - Remove the existing native material to sub-grade elevation beneath new proposed infrastructure.	C.Y.D.	8,963
8	Earthwork fill - Install native material to sub-grade elevation beneath new proposed infrastructure. Includes native material backing.	C.Y.D.	375
9	Sawcut the existing P.C.C. driveway for the full depth.	L.F.	173
10	Remove and dispose of existing P.C.C. driveway.	S.F.	2,169
11	Contractor to lower the existing sanitary sewer manhole frame and cover to 0.3' below finish grade prior to paving activities.	EACH	8
12	Contractor to lower the existing water valve riser to 0.3' below finish grade prior to paving activities	EACH	14
13	Remove and temporarily store existing signs to be relocated	EACH	5
14	Remove and dispose of existing 3-foot-high abandoned wire mesh fence.	L.F.	130
15	Sawcut the existing P.C.C. sidewalk for the full depth.	L.F.	29

ITEM NO.	ITEM	UNITS OF MEASURE	ESTIMATED QUANTITY
16	Remove and dispose of the existing P.C.C. sidewalk.	S.F.	2,237
17	Remove and dispose of existing P.C.C. handicap ramp.	S.F.	309
18	Sawcut the existing P.C.C. curb and gutter for the full depth.	L.F.	18
19	Remove and dispose of the existing P.C.C. curb and gutter.	L.F.	402
20	Adjust the existing water meter box to finish grade elevation.	EACH	6
21	Remove existing pavement striping.	LUMP SUM	1
22	Install A.C. pavement.	TONS	2,239
23	Install Class 2 Base material.	TONS	8,833
24	Install 6-inch P.C.C. curb and gutter including curb transitions.	L.F.	5,518
25	Install P.C.C. sidewalk.	S.F.	23,905
26	Install granular sand.	TONS	990
27	Install P.C.C. handicap ramp.	S.F.	2,770
28	Install detectable warning surface.	S.F.	240
29	Install P.C.C. driveway.	S.F.	11,752
30	Adjust the existing sanitary sewer manhole cover to finish grade.	EACH	8
31	Adjust the existing water valve risers to finish grade.	EACH	17
32	Install new P.C.C. cross gutter and spandrel.	S.F.	5,635
33	Grade the native material backing at new proposed improvements.	S.Y.D.	2,791
34	Adjust the existing sanitary sewer cleanout to finish grade elevation.	EACH	1
35	Striping and pavement markings	LUMP SUM	1
36	Install new temporary barricade and signs.	LUMP SUM	1
37	Install previously removed and stored signs.	EACH	6
38	Install "no idling" sign.	EACH	4
39	Install "pavement ends" sign.	EACH	1
40	Water pollution control - stormwater pollution prevention plan and erosion control bmps implementation. Include qualified SWPPP developer (QSD) and practitioner (QSP) inspection and reporting services.	LUMP SUM	1

ITEM NO.	ITEM	UNITS OF MEASURE	ESTIMATED QUANTITY
41	Temporary traffic control	LUMP SUM	1
42	Surveying and construction staking	LUMP SUM	1
43	Monument preservation	LUMP SUM	1
44	Time and material allocation	LUMP SUM	1

apparatus and other means of construction, and to do all the work and furnish all the materials specified in the contract, in the manner and time therein prescribed, and according to the requirements of the Engineer as therein set forth, and that he will take in full payment therefor the following prices, to wit:

BID ITEM LIST

ITEM NO.	ITEM	UNITS OF MEASURE	PRICE PER UNIT	ESTIMATED QUANTITY	TOTAL AMOUNT
1	Mobilization	LUMP SUM		1	
2	Clearing and grubbing	LUMP SUM		1	
3	Pot-hole existing utilities	LUMP SUM		1	
4	Sawcut the existing A.C. pavement for the full depth.	L.F.		4,230	
5	Cold plane existing A.C. pavement for a thickness of 0.20' min. Contractor to dispose of grindings.	S.F.		8,455	
6	Remove and dispose of existing A.C. pavement.	C.Y.D.		625	
7	Earthwork cut - Remove the existing native material to sub-grade elevation beneath new proposed infrastructure.	C.Y.D.		8,963	
8	Earthwork fill - Install native material to sub-grade elevation beneath new proposed infrastructure. Includes native material backing.	C.Y.D.		375	
9	Sawcut the existing P.C.C. driveway for the full depth.	L.F.		173	
10	Remove and dispose of existing P.C.C. driveway.	S.F.		2,169	
11	Contractor to lower the existing sanitary sewer manhole frame and cover to 0.3' below finish grade prior to paving activities.	EACH		8	
12	Contractor to lower the existing water valve riser to 0.3' below finish grade prior to paving activities	EACH		14	
13	Remove and temporarily store existing signs to be relocated	EACH		5	
14	Remove and dispose of existing 3-foot-high abandoned wire mesh fence.	L.F.		130	
15	Sawcut the existing P.C.C. sidewalk for the full depth.	L.F.		29	

16	Remove and dispose of the existing P.C.C. sidewalk.	S.F.		2,237	
17	Remove and dispose of existing P.C.C. handicap ramp.	S.F.		309	
18	Sawcut the existing P.C.C. curb and gutter for the full depth.	L.F.		18	
19	Remove and dispose of the existing P.C.C. curb and gutter.	L.F.		402	
20	Adjust the existing water meter box to finish grade elevation.	EACH		6	
21	Remove existing pavement striping.	LUMP SUM		1	
22	Install A.C. pavement.	TONS		2,239	
23	Install Class 2 Base material.	TONS		8,833	
24	Install 6-inch P.C.C. curb and gutter including curb transitions.	L.F.		5,518	
25	Install P.C.C. sidewalk.	S.F.		23,905	
26	Install granular sand.	TONS		990	
27	Install P.C.C. handicap ramp.	S.F.		2,770	
28	Install detectable warning surface.	S.F.		240	
29	Install P.C.C. driveway.	S.F.		11,752	
30	Adjust the existing sanitary sewer manhole cover to finish grade.	EACH		8	
31	Adjust the existing water valve risers to finish grade.	EACH		17	
32	Install new P.C.C. cross gutter and spandrel.	S.F.		5,635	
33	Grade the native material backing at new proposed improvements.	S.Y.D.		2,791	
34	Adjust the existing sanitary sewer cleanout to finish grade elevation.	EACH		1	
35	Striping and pavement markings	LUMP SUM		1	
36	Install new temporary barricade and signs.	LUMP SUM		1	
37	Install previously removed and stored signs.	EACH		6	
38	Install "no idling" sign.	EACH		4	
39	Install "pavement ends" sign.	EACH		1	
40	Water pollution control - stormwater pollution prevention plan and erosion control bmps implementation. Include qualified SWPPP developer (QSD) and practitioner (QSP) inspection and reporting services.	LUMP SUM		1	

41	Temporary traffic control	LUMP SUM		1	
42	Surveying and construction staking	LUMP SUM		1	
43	Monument preservation	LUMP SUM		1	
44	Time and material allocation	LUMP SUM		1	

Total _____